

# Simulating Visible/Infrared Imager/Radiometer Suite Normalized Difference Vegetation Index Data Using Hyperion and MODIS

Authors: Kenton Ross,<sup>1</sup> Jeffrey Russell,<sup>2</sup> and Robert E. Ryan<sup>1</sup>

<sup>1</sup> Science Systems and Applications, Inc., Stennis Space Center, MS 39529

<sup>2</sup> Computer Sciences Corporation, Stennis Space Center, MS 39529

POC: Kenton.W.Ross@nasa.gov

## Abstract

The success of MODIS (Moderate Resolution Imaging Spectroradiometer) in creating unprecedented, timely, high-quality data for vegetation and other studies has created great anticipation for data from VIIRS (the Visible/Infrared Imager/Radiometer Suite). VIIRS will be carried onboard the joint NASA/Department of Defense/National Oceanic and Atmospheric Administration NPP (NPOESS (National Polar-orbiting Operational Environmental Satellite System) Preparatory Project). Because the VIIRS instruments will have lower spatial resolution than the current MODIS instruments at nadir—400 m versus 250 m—for the channels used to generate Normalized Difference Vegetation Index data, scientists need the answer to this question: how will the change in resolution affect vegetation studies?

By using simulated VIIRS measurements, this question may be answered to a great degree before the VIIRS instruments are deployed in space. Using simulated VIIRS products, the U.S. Department of Agriculture and other operational agencies can then modify their decision support systems appropriately in preparation of receipt of actual VIIRS data. One pathway to achieving VIIRS simulations and validations is the ART (Application Research Toolbox), an integrated set of algorithms and models developed in MATLAB® that enables users to perform a suite of simulations and statistical trade studies on remote sensing systems. Specifically, the ART provides the capability to generate simulated multispectral image products, at various scales, from high spatial hyperspectral and/or multispectral image products. The ART uses acquired (i.e. “real”) or synthetic datasets, along with sensor specifications, to create simulated datasets. Existing data products (such as those from MODIS) can be generated to validate the simulation process.

In this study, VIIRS simulations were performed using Hyperion and MODIS datasets. The hyperspectral and hyperspatial properties of Hyperion data were used to produce simulated MODIS and VIIRS products. Hyperion-derived MODIS data were compared with near-coincident MODIS collects to validate spatial synthesis, which provided a basis to ascertain the accuracy of converting from MODIS to VIIRS. MODIS-derived VIIRS data is needed for global coverage and for the generation of time series for regional and global investigations. These types of simulations have errors associated with aliasing for some scene types. This study helps quantify these errors and identify common cases where high-quality, MODIS-derived VIIRS data can be effectively simulated.

## Problem

Vegetation monitoring applications that have begun to depend on daily MODIS data must convert VIIRS, but significant differences exist between the two instruments.

**MODIS:**  
Whiskbroom imaging radiometer  
Bands: 36 from 0.4 to 14.5  $\mu\text{m}$   
Spatial Resolution: 250 m; 500 m; 1,000 m  
Swath: 2,330 km  
Repeat Time: Global coverage in 1-2 days  
Design Life: 6 years


**VIIRS:**  
Whiskbroom imaging radiometer  
Bands: 22 between 0.3  $\mu\text{m}$  and 14  $\mu\text{m}$   
Spatial Resolution: 400 m and 800 m  
Swath: ~3,000 km  
Repeat Time: 1 day  
Design Life: 7 years

(NASA SSC, 2006)

## Capability: The Application Research Toolbox

e.g., AVIRIS, Hyperion, MODIS, etc.


(Blonski et al., 2002)



## Simulation Approach for VIIRS

- To satisfy the needs of data experiments requiring simulated VIIRS vegetation indices for high temporal frequency regional applications, multitemporal VIIRS red and near-infrared data from must be simulated from MODIS red and near-infrared bands. The initial simulation approach is limited to differences in spatial characteristics between the imaging systems, so PSF (point spread function synthesis and pixel degradation are applied.
- Initial simulation is based on nadir PSF only.


At-nadir PSFs for MODIS and VIIRS red bands are shown at right. The ART convolves the input MODIS data to the VIIRS PSF.



MODIS PSF based on on-orbit characterization by Rojas et al. (2002). VIIRS PSF based on anticipated performance as stated by Schueler et al. (2003).


## Two-Tiered Validation

Because no actual VIIRS data exists with which to test the simulation approach, it is necessary to validate with higher spatial/spectral fidelity data.




## Kenner, LA – VIIRS Simulation Test

Image data acquired on September 6, 2005. The MODIS data is from the MOD02 product and was acquired at 16:50 UTC. The Hyperion data was captured at 16:28 UTC.



## Results

- The MODIS case demonstrates expected results from higher spatial/spectral fidelity.
- The VIIRS case demonstrates that simulation of VIIRS from MODIS has its limitations. Spatially, MODIS does not meet the Nyquist criterion, so there are phasing errors in challenging scenes like this Kenner urban/rural mix.



## Conclusions

- The usefulness of the ART software is borne out by the excellent correlative results in simulating MODIS from coincident Hyperion.
- The simulation of VIIRS from MODIS performed reasonably well in a challenging scene. Better results can be expected in more homogeneous scenes such as one might expect in agricultural and forest-dominated landscapes.

## Next Steps

- Conduct additional validation experiments in areas of extensive large field agriculture and large managed timberlands to establish usefulness for vegetation monitoring.
- Update spatial simulation to more closely model the across-track variation of MODIS and VIIRS spatial characteristics.
- Refine metadata to more closely conform to that currently available for MODIS products.

## References

- Blonski, S., G. Gasser, J. Russell, R. Ryan, G. Terrie, and V. Zanoni, 2002. Synthesis of multispectral bands from hyperspectral data - validations based on images acquired by AVIRIS, Hyperion, ALI and ETM+. In *Proceedings of the 2002 AVIRIS Earth Science and Applications Workshop*, March 5–8, National Aeronautics and Space Administration, Jet Propulsion Laboratory, California Institute of Technology, Pasadena, CA, [http://popo.jpl.nasa.gov/pub/docs/workshops/02\\_docs/2002\\_Blonski\\_web.pdf](http://popo.jpl.nasa.gov/pub/docs/workshops/02_docs/2002_Blonski_web.pdf) (accessed November 20, 2006).
- NASA SSC [Stennis Space Center], 2006. *Earth-Sun Science System Components Knowledge Base*. <http://www.esa.ssc.nasa.gov/m2m/> (accessed November 20, 2006).
- Rojas, F., R.A. Schowengerdt, and S.F. Biggar, 2002. Early results on the characterization of the Terra MODIS spatial response. *Remote Sensing of Environment* 83:50–61.
- Schueler, C., J.E. Clement, L. Darnton, F. DeLuccia, T. Scalione, and H. Swenson, 2003. VIIRS sensor performance. In *Proceedings: 2003 IEEE International Geoscience and Remote Sensing Symposium*, 21–25 July, vol. 1, pp. 369–372.

## Related Poster & Presentation

- Prados, D., R.E. Ryan, and K.W. Ross, 2006. Remote Sensing Time Series Product Tool. *Eos Transactions AGU*, 87(52), Fall Meeting Supplement, Abstract IN33B-1341. (poster)
- O'Hara, C.G., R. Moorhead, D. Shaw, B. Shrestha, K.W. Ross, D. Prados, J. Russell, and R.E. Ryan, 2006. Integrated use of tools and technologies for rapidly prototyping simulated data products of future NASA observing systems for evaluation in application of national importance. *Eos Transactions AGU*, 87(52), Fall Meeting Supplement, Abstract IN32A-05. (presentation, Session IN32A, Wednesday, Dec. 13, 11:20)



REPORT DOCUMENTATION PAGE					Form Approved OMB No. 0704-0188	
<p>The public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.</p> <p><b>PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.</b></p>						
1. REPORT DATE (DD-MM-YYYY) 22-11-2006		2. REPORT TYPE Conference Poster		3. DATES COVERED (From - To) 05/2006 - 11/2006		
4. TITLE AND SUBTITLE Simulating Visible/Infrared Imager Radiometer Suite Normalized Difference Vegetation Index Data Using Hyperion and MODIS				5a. CONTRACT NUMBER NASA Task Order NNS04AB54T		
				5b. GRANT NUMBER		
				5c. PROGRAM ELEMENT NUMBER		
6. AUTHOR(S) Ross, Kenton W. (1); Russell, Jeffrey (2); Ryan, Robert E. (1)				5d. PROJECT NUMBER		
				5e. TASK NUMBER		
				5f. WORK UNIT NUMBER SWR UX00-SS02-00		
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) NASA John C. Stennis Space Center, MS 39529 Science System and Applications Inc., Bldg. 1105, John C. Stennis Space Center, MS 39529 (1) Computer Sciences Corporation, Bldg. 1105, John C. Stennis Space Center, MS 39529 (2)				8. PERFORMING ORGANIZATION REPORT NUMBER  SSTI-2220-0089-R		
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration, Washington, DC 20546-0001				10. SPONSORING/MONITOR'S ACRONYM(S)  NASA		
				11. SPONSORING/MONITORING REPORT NUMBER		
12. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Category 43 Availability: NASA CASI (301) 621-0390						
13. SUPPLEMENTARY NOTES 2006 AGU Fall Meeting, 11-15 December 2006, San Francisco, CA, USA						
14. ABSTRACT VIIRS simulations and validations will be based on the Application Research Toolbox, an integrated set of algorithms and models developed in MATLAB® that enables users to perform a suite of simulations and statistical trade studies on remote sensing systems. The hyperspectral and hyperspatial properties of Hyperion data will be used to produce simulated MODIS and VIIRS products. Hyperion-derived MODIS data will be compared with near-coincident MODIS collects to validate both spectral and spatial synthesis, which will ascertain the accuracy of converting from MODIS to VIIRS.						
15. SUBJECT TERMS remote sensing, VIIRS, MODIS, Hyperion, NDVI, vegetation, simulation						
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19b. NAME OF RESPONSIBLE PERSON	
a. REPORT	b. ABSTRACT	c. THIS PAGE			STI Help Desk at email: help@sti.nasa.gov	
U	U	U	UU	1	19b. TELEPHONE NUMBER (Include area code) (301) 621-0390	